

Elitech[®]

Operating Instruction (TPM-10F)

Features

- LCD display.
- Insert design.
- Simple appearance.
- Two button batteries for longer use time.
- Especially applied in refrigerator, chiller, deepfreeze etc.

Technical parameter

- Temperature range: -50℃~+80℃
- Using environment: Temperature: -5℃~+50℃
Humidity: 5%~80%
- Accuracy: ±1℃ (-20℃~+40℃)
±2℃ (-50℃~-20℃, +40℃~+80℃)
- Resolution: 1(≤-20℃) 0.1(>-20℃)
- Power: two button battery (LR44,1.5v)

Instruction

- Open the battery cover to put in two LR44 batteries correctly, pay attention to the polarity.
- Display when put in the batteries. Pls take out the batteries when not use for long time
- LCD display "--.℃" when temperature is lower than -50℃.
- Insert size: 46 x 26.6mm

Jiangsu Jingchuang Electronics Co.,Ltd.

V1.4

刀模线
不印刷

媒体编号

旧图纸总号

底图总号

拟制
审核

日期 签名

标准化
批准

格式 (4)

制图:

描图:

幅面:

标记 数量 更改单号 签名 日期

JY-8.805.214

25060122901

阶段 标记 第 1 张 共 1 张

S

A

TPM-10F英文说明书
(常规)